

&lt;400 g/l SATIN &amp; GLOSS ACRYLIC LACQUER

Page: 1  
10/12/2013

PRODUCT NAME: <400 g/l SATIN & GLOSS ACRYLIC LACQUER                      HMIS CODES: H F R P  
PRODUCT CODE: AWR-3 VOC SATIN, AWR-3 GLOSS VOC & AWR-2 VOC                      2 3 0 G

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: AMTECO, INC.  
DISTRIBUTED BY : FSC Coatings, Inc.  
5360 EASTGATE MALL, STE F  
SAN DIEGO, CA 92121  
EMERGENCY PHONE : 1-800-424-9300                      DATE PRINTED : 10/12/2013  
INFORMATION PHONE : 1-800-579-8459                      NAME OF PREPARER : N/A

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
PARACHLOROBENZOTRIFLUORIDE OSHA PEL: N/A, ACGIH TLV: N/A, OTHER: N/A	98-56-6	5.3      20 C	10
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC OSHA PEL: 25 PPM TWA      15 PPM STEL ACGIH TLV: 25 PPM TWA      15 PPM STEL	64742-94-5	5.2      100 F	8
PROPYLENE GLYCOL METHYL ETHER ACETATE OSHA PEL: NE, ACGIH TLV: NE, OTHER: NE	108-65-6	3.8      77 F	2

PAINT, 3, UN 1263, PG.II EMG GUIDE #128

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 282 F - 355-420 F                      SPECIFIC GRAVITY (H2O=1): 1.219  
VAPOR DENSITY: HEAVIER THAN AIR                      EVAPORATION RATE: SLOWER THAN ETHER  
COATING V.O.C.: 3.3 lb/gl                      MATERIAL V.O.C.: 1.1 lb/gl  
SOLUBILITY IN WATER: INSOLUBLE  
APPEARANCE AND ODOR:

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 109 F                      METHOD USED: TCC  
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.9                      UPPER: 10.5

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

WEAR A SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE-PIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WITH APPROPRIATE TURN-OUT GEAR AND CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT.

UNUSUAL FIRE AND EXPLOSION HAZARDS

WATER MAY BE USED TO COOL CONTAINERS. VAPORS MAY CAUSE FLASH FIRES. KEEP CONTAINERS TIGHTLY CLOSED AND ISOLATE FROM HEAT, SPARKS AND FLAME. NEVER USE WELDING OR CUTTING TORCH ON OR NEAR CONTAINERS EVEN IF EMPTY. RESIDUE CAN STILL IGNITE.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

AVOID CONTACT WITH STRONG OXIDIZERS, HIGH TEMPERATURES AND OPEN IGNITION SOURCES.

INCOMPATIBILITY (MATERIALS TO AVOID)

OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION OF VAPOR OR MIST CAN CAUSE THE FOLLOWING:

IRRITATION TO THE UPPER RESPIRATORY TRACT, MAY CAUSE NAUSEA, HEADACHE, FATIGUE, LOSS OF APPETITE. HIGH CONCENTRATIONS CAN CAUSE COLLAPSE, BRONCHITIS, PNEUMONIA AND CONVULSIONS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN: CAN CAUSE IRRITATION. CAN CAUSE DEFATTING OF SKIN, WHICH CAN LEAD TO DERMITITIS.

EYE: LIQUID AND VAPOR CAN BE IRRITATING TO EYES. SYMPTOMS INCLUDE TEARING, REDNESS AND DISCOMFORT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

THIS PRODUCT IS NOT EASILY ABSORBED. PROLONGED CONTACT MAY RESULT IN THE EXTRACTION OF NATURAL OILS CAUSING IRRITATION AND DRYNESS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

TOXIC IF SWALLOWED. WILL CAUSE VOMITING, NAUSEA, DIARRHEA. HIGH CONCENTRATIONS CAN CAUSE COLLAPSE, PNEUMONIA AND CONVULSIONS.

HEALTH HAZARDS (ACUTE AND CHRONIC)

BREATHING DIFFICULTIES, DIZZINESS, LOSS OF COORDINATION AND HEADACHE ARE SIGNS OF EXPOSURE TO CONCENTRATIONS ABOVE THE TLV. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVER EXPOSURE WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

CARCINOGENICITY: NTP CARCINOGEN: N/A IARC MONOGRAPHS: N/A OSHA REGULATED:  
N/A

N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

PRE-EXISTING DISORDERS OR DISEASES OF THE SKIN, EYE, LIVER, KIDNEY, NERVOUS SYSTEM, RESPIRATORY AND/OR PULMONARY SYSTEM, LUNG (E.G. ASTHMA-LIKE CONDITIONS).

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: MOVE SUBJECT TO FRESH AIR. RESTORE BREATHING IF NECESSARY. TREAT SYMPTOMATICALLY AND CONSULT PHYSICIAN. EYE & SKIN CONTACT: FLUSH EYES WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES. SEE A PHYSICIAN IMMEDIATELY. WASH SKIN

AFTER REMOVING CONTAMINATED CLOTHING WITH MILD SOAP AND WATER FOR 15 MINUTES. SEE PHYSICIAN IF IRRITATION PERSISTS.  
INGESTION: DRINK 1-2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY. NEVER GIVE LIQUIDS TO AN UNCONSCIOUS PERSON.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

STOP SPILL AT SOURCE. ELIMINATE ALL IGNITION SOURCES (FLARES, OPEN FLAMES, PILOT LIGHTS, ELECTRICAL SPARKS). USE ONLY NON SPARKING TOOLS FOR CLEAN UP. SUPPLY ADEQUATE VENTILATION. AVOID BREATHING OF VAPORS, USE RESPIRATOR. CONTAIN AND REMOVE WITH INERT ABSORBENT.

WASTE DISPOSAL METHOD

DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP ALL CONTAINERS SEALED TIGHT AND IN AN UPRIGHT POSITION TO PREVENT LEAKS. STORE CONTAINERS OUT OF SUN AND AWAY FROM ALL HEAT SOURCES. THIS MATERIAL SHOULD BE GROUNDED WHEN POURING. DO NOT STORE NEAR HEAT, SPARKS OR OPEN FLAME.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS OR SPRAY MIST. WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING APPLICATION AND OTHER USE OF THIS MATERIAL UNTIL VAPORS AND MISTS ARE EXHAUSTED AND EXPOSURE IS BELOW LISTED TLV(S). USE APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICLES AND VAPORS.

VENTILATION

PROVIDE SUFFICIENT VENTILATION TO KEEP VAPOR CONCENTRATIONS BELOW GIVEN TLV AND LEL LEVELS. IF LOCAL EXHAUST DOES NOT KEEP VAPOR CONCENTRATIONS BELOW LISTED LEVELS MECHANICAL EXHAUST IS REQUIRED.

PROTECTIVE GLOVES

IMPERMEABLE CHEMICAL RESISTANT GLOVES SUCH AS NEOPRENE COATED GLOVES.

EYE PROTECTION

USE SAFETY EYE WARE WITH SIDE-SHIELDS TO PROTECT AGAINST CHEMICAL SPLASH OF LIQUIDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

EYE BATH AND SHOWERS SHOULD BE READILY AVAILABLE. USE CHEMICAL RESISTANT APRON, BOOTS OR OTHER CLOTHING NEEDED TO AVOID REPEATED OR FREQUENT SKIN CONTACT. LIQUID MAY PENETRATE SHOES AND LEATHER CAUSING DELAYED IRRITATION.

WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE AND AFTER EATING, SMOKING AND USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, AMTECO, INC. DOES NOT ASSUME ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER.