

M A T E R I A L   S A F E T Y   D A T A   S H E E T

PRODUCT NAME: SILOX SEAL "A" SIDE  
PRODUCT CODE: SILOX SEAL-A SIDE

HMIS CODES: H F R P  
1 0 0 G

=====  
SECTION I - MANUFACTURER IDENTIFICATION  
=====

MANUFACTURER'S NAME: AMTECO, INC.  
DISTRIBUTED BY : 5360 EASTGATE MALL, STE F  
SAN DIEGO, CA 92121  
EMERGENCY PHONE : 1-800-424-9300      DATE PRINTED : 1/12/2014  
INFORMATION PHONE : 1-800-579-8459      NAME OF PREPARER : N/A

=====  
SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION  
=====

REPORTABLE COMPONENTS	CAS NUMBER	WEIGHT PERCENT
-----------------------	------------	----------------

-----  
-----

\*\*\* NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT \*\*\*  
PAINT, NON HAZARDOUS - NOT REGULATED

=====  
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS  
=====

BOILING RANGE: N/A .9925	SPECIFIC GRAVITY (H2O=1):
VAPOR DENSITY: HEAVIER THAN AIR ETHER	EVAPORATION RATE: SLOWER THAN
COATING V.O.C.: 1.76 lb/gl	MATERIAL V.O.C.: 0.2 lb/gl
SOLUBILITY IN WATER: SOLUBLE	
APPEARANCE AND ODOR: MILKY WHITE LIQUID VERY MILD ODOR	

=====  
SECTION IV - FIRE AND EXPLOSION HAZARD DATA  
=====

FLASH POINT: N/A	METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A	UPPER: N/A

EXTINGUISHING MEDIA: USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.

SPECIAL FIREFIGHTING PROCEDURES  
THIS PRODUCT WILL NOT SUPPORT COMBUSTION

UNUSUAL FIRE AND EXPLOSION HAZARDS  
MATERIAL CAN SPLATTER ABOVE 100C/212F. DRIED PRODUCT CAN BURN.

=====  
SECTION V - REACTIVITY DATA  
=====

STABILITY: STABLE  
CONDITIONS TO AVOID  
NONE KNOWN

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE KNOWN

HAZARDOUS DECOMPOSITION OR BYPRODUCTS  
CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

=====  
SECTION VI - HEALTH HAZARD DATA  
=====  
INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
INHALATION OF VAPOR OR MIST CAN CAUSE THE FOLLOWING:  
HEADACHE-NAUSEA-IRRITATION OF NOSE, THROAT AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
EYE CONTACT-DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION AND DRYNESS.  
SKIN CONTACT-PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE MILD  
IRRITATION AND  
DRYNESS.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE MILD IRRITATION AND  
DRYNESS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
MAY CAUSE NAUSEA AND VOMITING.

HEALTH HAZARDS (ACUTE AND CHRONIC)  
NOT KNOWN

CARCINOGENICITY:NTP CARCINOGEN: N/A IARC MONOGRAPHS:N/A OSHA  
REGULATED:N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE  
NOT KNOWN

EMERGENCY AND FIRST AID PROCEDURES  
INHALATION: MOVE SUBJECT TO FRESH AIR. RESTORE BREATHING IF NECESSARY.  
TREAT  
SYMPTOMATICALLY AND CONSULT PHYSICIAN. EYE & SKIN CONTACT: FLUSH EYES  
WITH LARGE  
AMOUNT OF WATER FOR AT LEAST 15 MINUTES. SEE A PHYSICIAN IMMEDIATELY.  
WASH SKIN  
AFTER REMOVING CONTAMINATED CLOTHING WITH MILD SOAP AND WATER FOR 15  
MINUTES.  
SEE PHYSICIAN IF IRRITATION PERSISTS. INGESTION: DRINK 1-2 GLASSES OF  
WATER TO  
DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL  
CENTER  
IMMEDIATELY. TREAT SYMPTOMATICALLY. NEVER GIVE LIQUIDS TO AN  
UNCONSCIOUS PERSON.

=====  
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE  
===

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  
KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY; USE CARE TO AVOID  
FALLING. CONTAIN  
SPILLS IMMEDIATELY WITH INERT MATERIALS (E.G. SAND, EARTH). TRANSFER  
LIQUIDS AND  
SOLID DIKING MATERIAL TO SEPARATE SUITABLE CONTAINERS FOR RECOVERY OR  
DISPOSAL.

WASTE DISPOSAL METHOD  
DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING  
KEEP FROM FREEZING.

OTHER PRECAUTIONS  
DO NOT TAKE INTERNALLY

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

A RESPIRATORY PROTECTION PROGRAM MEETING OSHA 1910.134 AND ANSI Z88.2  
REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A  
RESPIRATOR'S USE. NONE REQUIRED IF AIRBORNE CONCENTRATIONS ARE  
MAINTAINED BELOW  
THE EXPOSURE LIMIT LISTED IN "EXPOSURE LIMIT INFORMATION", WEAR A  
MSHA/NIOSH  
APPROVED (OR EQUIVALENT) HALF-MASKED, AIR-PURIFYING RESPIRATOR. IF NO  
EXPOSURE  
LIMITS ARE LISTED, THEN NO RESPIRATOR IS NEEDED.

VENTILATION

USE LOCAL EXHAUST VENTILATION WITH A MINIMUM CAPTURE VELOCITY OF 100  
FT/MIN.  
(0.5 M/SEC.) AT THE POINT OF VAPOR EVOLUTION.

PROTECTIVE GLOVES

NEOPRENE GLOVES RECOMMENDED FOR DIRECT CONTACT.

EYE PROTECTION

USE CHEMICAL SPLASH GOGGLES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

FACILITIES STORING OR UTILIZING THIS MATERIAL SHOULD BE EQUIPPED WITH  
AN EYE  
WASH STATION AND SHOWER.

WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE AND AFTER EATING, SMOKING AND USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS  
ACCURATE.  
HOWEVER, AMTECO, INC. DOES NOT ASSUME ANY LIABILITY WHATSOEVER FOR THE  
ACCURACY  
OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL  
DETERMINATION OF  
SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER.